



RUGGED. RELIABLE. REAL.

HT66KX

FEATURES

- 11,000 LB Maximum Lifting Capacity
- 66,000 FT-LB Moment Rating
- Fully Hydraulic Power
- Hexagonal Boom Construction
- Fully Hydraulic Boom Extension 12' – 25' FT
- High Speed Winch: 66 FT/min.
- 400 Power Rotation
- Meets ANSI B30.5 Safety Standards
- Meets OSHA 1910.180 Requirements

LIFTING CAPACITIES	
REACH (FT.)	CAPACITY (LBS.)
6	11,000
12	5,500
18.5	3,550
24.8	2,650

STANDARD EQUIPMENT

- Capacity Overload Shut-Off System
- Anti-Two-Blocking System
- 100 FT of 7/16" Aircraft-Quality Wire Rope
- Remote Control Pendant: 25 FT Cord and Quick Disconnect
- Load Block with Swivel Hook Safety Latch

MINIMUM REQUIREMENTS

- 33,000 LB GVWR Chassis
- Outriggers: Front and Rear
- PTO, Pump and Reservoir
- Hydraulic Requirements: 12 GPM, 25 GAL Reservoir

OPTIONAL EQUIPMENT

- Radio Remote Controls
- Hydraulic and Manual Outrigger Packages
- Hydraulic Pumps and Reservoirs
- Mounting Pedestal for Platform Bodies
- Boom Rests

