



VC516

SPECIFICATIONS

- For 8' – 12' bodies
- 8 – 17 Ton capacity
- Available with 4" or 5" cylinder and 16" stroke
- Low mounting height scissors design with narrow drop hinge knuckle
- Pre-installed self-locating body prop
- Fits 29 ½" – 34" truck frames
- 7" Subframe mounting height
- Includes 4" Subframe rail
- Conversion Class C
- Dump Class 20
- High pressure, double-acting cylinder with 5" bore x 16" stroke and multi-hard chromed and polished piston rod
- Mounting height 5 ¾"
- Pumps: Electric single-acting, 6 qt. reservoir
 - Electric double-acting, 4 qt. reservoir
 - 4 piston PTO driven, 7/8" square shaft, 7qt. reservoir
 - Direct mount gear PTO driven, SAE "A" 2 bolt flange, 5/8" -9 spline shaft 9 qt. reservoir
- Operating pressure: 3000/1000 PSI
- Weight:
 - VC516 – 385 lbs.
 - VC516 w/SF – 485 lbs.



CAUTION: THE COMBINED WEIGHTS OF TRUCK, BODY, HOIST AND LOAD MUST NOT EXCEED THE GROSS VEHICLE WEIGHT RATING (GVWR) OF THE TRUCK.

12110 Best Place | Cincinnati, Ohio 45241 | 800-226-2238 | 513-772-8446
info@venturo.com | www.venturo.com