



VC520

SPECIFICATIONS

- For 12' – 15' bodies
- 8 – 14 Ton capacity
- Available with 5" cylinder and 20" stroke
- Low mounting height scissors design eliminates interference with chassis components.
- Pre-installed self-locating body prop
- Fits 29 ½" – 34" truck frames
- 7 ½" Subframe mounting height
- Includes 4" Subframe rail
- Conversion Class D
- Dump Class 40
- High pressure, double-acting cylinder with 5" bore x 20" stroke and multi-hard chromed and polished piston rod
- Mounting height 7 ½"
- Pumps: Electric single-acting, 6 qt. reservoir
 - Electric double-acting, 4 qt. reservoir
 - 4 piston PTO driven, 7/8" square shaft, 15 qt. reservoir
 - Direct mount gear PTO driven, SAE "A" 2 bolt flange, 5/8" -9 spline shaft 9 qt. reservoir
- Operating pressure: 3200/1000 PSI
- Weight:
 - VC520 – 450 lbs.
 - VC520 w/SF – 570 lbs.



CAUTION: THE COMBINED WEIGHTS OF TRUCK, BODY, HOIST AND LOAD MUST NOT EXCEED THE GROSS VEHICLE WEIGHT RATING (GVWR) OF THE TRUCK.

12110 Best Place | Cincinnati, Ohio 45241 | 800-226-2238 | 513-772-8446
internetsales@venturo.com | www.venturo.com