



# VC620

## SPECIFICATIONS

- For 12' – 16' bodies
- 10 – 20 Ton capacity
- Available with 6" cylinder and 20" stroke
- Low mounting height scissors design eliminates interference with chassis components.
- Pre-installed self-locating body prop
- Fits 29 ½" - 34" truck frames
- 9 ¾" Subframe mounting height
- Includes 4" Subframe rail
- Conversion Class E
- Dump Class 50
- High pressure, double-acting cylinder with 6" bore x 20" stroke and multi-hard chromed and polished piston rod
- Mounting height 8"
- Pumps:
  - Direct-mount gear PTO driven, SAE "A" 2 bolt flange, 5/8" – 9 spline shaft, 21 qt. reservoir
  - Electric single-acting, H.D. motor, 8 qt. reservoir
  - Electric double-acting, H.D. motor, 4 qt. reservoir
- Operating pressure: 3000/1000 PSI
- Weight:
  - VC620 – 625 lbs.
  - VC620 w/SF – 745 lbs.



**CAUTION: THE COMBINED WEIGHTS OF TRUCK, BODY, HOIST AND LOAD MUST NOT EXCEED THE GROSS VEHICLE WEIGHT RATING (GVWR) OF THE TRUCK.**

12110 Best Place | Cincinnati, Ohio 45241 | 800-226-2238 | 513-772-8446  
[info@venturo.com](mailto:info@venturo.com) | [www.venturo.com](http://www.venturo.com)