



VP/VC 6600

SPECIFICATIONS

- Complete custom engineering, ensuring proper installation and perfect fit
- Heavy duty 6,000 lb. capacity
- 45° dumping angle
- Integrated hinge and bumper brackets
- Greaseless composite bearings in the hinges
- Integrated lifting nest, hinge assembly and body stiffener forms rugged body understructure to rigidly support pickup floor
- Bumper relocation kit maintains original look of vehicle and Class II hitch rating
- In-cab electronic controls; handheld pendant controller comes standard
- Safety prop (standard)
- New design requires minimal welding, speeding installation by an hour or more
- 3 1/2" diameter cylinder, 12-7/8" stroke operating at 2800 PSI (Double acting option operates at 650 PSI down pressure)
- Factory assembled variable width mounting base adapts to original cross member
- One-piece unitized upper nest insures maximum support to pickup body
- Built-in tapered guides standard
- Heavy-duty 12 volt electric hydraulic single-acting and double-acting pumps



CAUTION: THE COMBINED WEIGHTS OF TRUCK, BODY, HOIST AND LOAD MUST NOT EXCEED THE GROSS VEHICLE WEIGHT RATING (GVWR) OF THE TRUCK.

12110 Best Place | Cincinnati, Ohio 45241 | 800-226-2238 | 513-772-8446
info@venturo.com | www.venturo.com