

# TRUCK HOISTS SR-4016

www.rugbymfg.com









## **SUBFRAME SCISSOR HOIST**

### **NEW SR-4016 TRUCK HOIST!**

With over 45 years of experience, Rugby® is the industry leader in hoist design and testing. The new Rugby SR-4016 truck hoist is tested at full-rated capacity for an extended life cycle\*, and with a new integrated body prop, the SR-4016 will reduce the installation time in your shop by at least 10-15%! The new SR-4016 can be used for both HR520 and HR540 applications, reducing your inventory!

- NTEA Classification: Conversion = D/Dump Body = 40
- Approximate weight: 460 lbs.\*\* weight savings of up to 20%
- Available with single or double acting electric pump or direct mount gear pump
- Cylinder specifications: 5.5" bore; 16" stroke; 2" diameter rod
- Mounting height: 9.6 inches
- Capacity range: 7.7 17 tons
- Factory tested for durability & performance
- Integrated body prop no installation required

\*Test results assume all recommended maintenance is adhered to.

\*\*Weight includes hoist, subframe, and mounting components.





Factory Tested for Performance & Durability

> Integrated **Body Prop**

IDra

Fully Greaseable **Pivot Points** 

Rugby - World Class Leader in Hoist Design



#### **SR-4016 SUBFRAME** SCISSOR HOIST

Body Length	CA	Rear Overhang	Capacity 50° Dump
8'	60"	6"	12.1T
9'	60"	6"	10.6T
9'	60"	18"	14.1T
10'	60"	30"	17.0T
10'	84"	6"	9.4T
11'	84"	6"	8.5T
11'	84"	18"	10.5T
12'	84"	18"	9.4T
12'	84"	30"	12.1T
12'	108"	6"	7.7T
14'	108"	18"	7.7T
Mounting Distance			72"

All specifications are subject to change without notice.



**RUGBY MANUFACTURING** Rugby, ND • 701-776-5722 • FAX 701-776-6235

www.rugbymfg.com • E-mail sales@rugbymfg.com



Sold by:

**Double Acting** Cylinders with Hardened Chrome **Cylinder Shafts**