



# RE 50,7



- Rated Line pull 50,7 kN
- Recommended cable 10 mm
- 12' (3,65 m) Remote Included
- EN 14492-1 Compliant
- Made in the USA

## RE 50,7 Features

- Rugged worm gear design for long life
- Motor and solenoids are grounded directly to battery
- Exclusive semi-automatic RAM-LOK™ clutch disengages for free spooling
- Weather resistant solenoid assembly
- 12 ft. (3,65 m) wire pendant remote included
- 6 ft. (1,83 m) 2 gauge battery cables with connectors
- 4-way roller fairlead
- Available at 12V or 24V with or without fairlead

## Specifications

Rated Line Pull	50,7 kN
Gear Reduction	470:1
Weight	61 kgs

LAYER OF CABLE		1	2	3
*RATED LINE PULL PER LAYER	kN	50.7	41.8	36.0
*CABLE CAPACITY	M	4	12	21
*CABLE CAPACITY X DRUM	M	7	16	28
*FIRST LAYER LINE SPEED 12V	MPM	1.0	1.2	1.3
*FIRST LAYER LINE SPEED 24V	MPM	0.6	0.7	1.0

\*These specifications are based on recommended wire rope of 10 mm 1960 grade wire rope.

## Winch Dimensions

